#### **NISTIR 6527**

# Measurement Needs for Fire Safety: Proceedings of an International Workshop

Thomas J. Ohlemiller Erik L. Johnsson Richard G. Gann



### Measurement Needs for Fire Safety: Proceedings of an International Workshop

Thomas J. Ohlemiller
Erik L. Johnsson
Richard G. Gann
Building and Fire Research Laboratory
National Institute of Standards and Technology
Gaithersburg, MD 20899-8653

June 2000



U.S. Department of Commerce William M. Daley, Secretary

Technology Administration

Dr. Cheryl L. Shavers, Under Secretary of

Commerce for Technology

National Institute of Standards and Technology Raymond G. Kammer. Director

#### NOTICES:

Works of authors who are not staff members of NIST are provided for information purposes.

NIST is not responsible for their content.

The identification of any commercial product or trade name does not imply endorsement or recommendation by the National Institute of Standards and Technology, nor is it intended to imply that the product identified is necessarily the best available for the purpose.

### **In-Situ Gas Concentration Measurements for Fires**

Linda G. Blevins
linda.blevins@nist.gov
Building and Fire Research Laboratory
April 6, 2000

Sectional testitute of Stonatoric and Technology



### Definition of In-Situ

- Not intrusive
- Does not alter environment
- · Involves lasers and detectors
- Employs spectroscopy

NST



### Selecting a Method

- Consider application: bench scale experiment, product test, reduced scale enclosure, full scale burns
- What are you measuring? How much is there? What is the temperature?
- · What other things are there? gases, early soot, mature soot, droplets
  - these could be interferences
  - also could attenuate or steer light
- · Optical Access Possibilities
- \$\$\$\$\$ Budget ..... Time Budget
- Available Expertise? technician, engineer, trained MS or PhD laser diagnostician
- · Many applications require two or more methods


NIST

rational teathure of Stendards and Technology



### **Comments on Accuracy**

- Major uncertainty sources are systematic errors associated with converting a measured quantity into a concentration
  - temperature effects
  - collisional environment
  - laser power fluctuation, laser line center/shape drift
  - soot extinction, beam steering/defocusing
- · Accuracy sometimes expressed as "detection limit"



### **Spontaneous Raman Scattering**

- · Used for Major Species Concentrations
  - H<sub>2</sub>, N<sub>2</sub>, O<sub>2</sub>, CH<sub>4</sub>, CO<sub>2</sub>, CO
- · Inelastic scattering of laser light by molecules
  - Incoherent (scatters in every direction)
  - No specific  $\lambda_{laser}$  is required, although lower  $\lambda_{laser} \Rightarrow higher signal$
  - Scattering at  $\lambda_{emission} > \lambda_{taser}$  (Stokes) and  $\lambda_{emission} < \lambda_{taser}$  (Anti-Stokes)
  - Several molecules detectable by monitoring several  $\lambda_{emission}$  simultaneously
  - Suffers interference from PAH LIF, Other Raman, Rayleigh
  - Can suffer interference from wall & particulate scattering
  - Weak Signals
- Temporal resolution =>  $(typ. < 1 \mu s)$  => determined by detector gate or laser
- Spatial resolution => (typ. < 1 mm<sup>3</sup>) => determined by collection optics
- Often Combined with Rayleigh Scattering for Temperature & Concentration

NUST Stational teathure of Standards and Technology Proceedings Associates Story, U.S. Dodardnos of Comments

**4** 

### Rayleigh Scattering

- Signal proportional to total ρ -- all molecules contribute
- · Used primarily for Temperature
- · Can be used for gas concentration in isothermal binary mixtures
- Elastic scattering of laser light by molecules (λ<sub>emission</sub> = λ<sub>laser</sub>)
  - Incoherent (scatters in every direction)
  - Requires clean environment
  - Signal much stronger than Raman Scattering
- Temporal resolution => (typ.  $< 1 \mu s$ ) => determined by detector gate or laser
- Spatial resolution => (typ. < 1 mm<sup>3</sup>) => determined by collection optics
- Can suffer interference from wall & particulate scattering

NIST

### Laser Induced Fluorescence (LIF)

- Used for Minor Species Concentrations
  - OH, CH, NO, CO routinely probed
  - Also possible to probe H2, O2, H2O, O, H & other atoms
  - Mixing tracers such as added acetone
- Laser light => photon absorbed by molecule => light emitted
  - A molecule can have several  $\lambda_{emission}$  (same & different from  $\lambda_{laser}$ )
  - Incoherent (emitted in all directions)
  - Orders of magnitude stronger signals than Raman scattering
  - Sensitive to quenching
- Temporal resolution => (typical < 1 μs) => determined by detector gate or fluorescence lifetime
- Spatial resolution => (typical < 1 mm<sup>3</sup>) => determined by collection optics
- · Can suffer interference from PAH LIF, Rayleigh
- · Can suffer interference from wall & particulate scattering


NIST

estimal testitute of Standonic and Scotnology



### **Planar Imaging Measurements**

- CH, C<sub>2</sub>, CN, NO, H, O, CO, Tracers (acetone)
- · Mostly qualitative
- Planar Rayleigh, Planar LIF (PLIF)
- Can be performed simultaneously with planar velocimetry
- Suffer from Raman, Rayleigh, LIF interference sources
- PLIF requires intensified CCD cameras



**SNL** Website

NIST

Kutumud Sandandu of Strander de and Bernandugg Interdoor autologischen VS. Description of Controls



### Coherent Anti-Stokes Raman Scattering (CARS)


- Used for Major Species N<sub>2</sub>, O<sub>2</sub>, CO, H<sub>2</sub>, H<sub>2</sub>O concentrations > 1% vol
- 2 or 3 incident laser beams with special  $\lambda_{laser}$ 
  - Produce a coherent (directional) signal beam with an additional λ
  - Can be used in mildly sooting environments
  - Multiple species and/or temperature
  - Signal orders of magnitude stronger than spontaneous Raman
  - Complicated spectra/signal processing
  - Suffers from non-resonant spectral background interference
- Spatial Resolution: Defined by laser overlap geometry (typical ~ 1 mm²)
- Temporal Resolution: (typical  $< 1 \mu s$ ) defined by detector gate or laser pulse
- Accuracy: detection limit ~1%

NUST

kerienak taatikon el Standondo and technology



## Laser Induced Breakdown Spectroscopy (LIBS)




- Spectrometer
- Uses spectral information to measure multiple metals
- · Good for inorganic species
- Temporal resolution 

  plasma lifetime ≈ 100 

  µs
- Spatial resolution ≈ 2 mm
- Detection limits O(ppb)

- Line position provides species identification
- Line intensity provides species concentration




Wavelength (nm)

NST

Dr. Steven Buckley, buckley@eng.umd.edu



### Tunable Diode Laser Absorption (TDLAS)



- fiber optics
- low-cost miniature lasers
- · water-cooled
- · purged optics
- quantifiable spatial & temporal resolution
- quantifiable uncertainty
- · fast measurements
- use in sooty environments
- detect multiple species simultaneously

NUST Stational testitute of Standards and Technology



### **Laser Absorption Spectroscopy**

- · Laser photon absorbed by molecule
  - traditionally performed using lamps
  - path-averaged measurement
  - now performed with tunable diode lasers
- · Near-infrared communication lasers: spectrally narrow
  - H<sub>2</sub>O, T, soot, CO, O<sub>2</sub>, CO<sub>2</sub>, CH<sub>4</sub>, C<sub>2</sub>H<sub>2</sub>, C<sub>2</sub>H<sub>4</sub>
     also HCN, HCl, NO, NO<sub>2</sub>, OH, H<sub>2</sub>S, NH<sub>3</sub>
- Lasers => narrow spectral coverage
  - ~2.5 nm (10 cm<sup>-1</sup>) for temperature-tuning
  - ~0.5 nm (2 cm<sup>-1</sup>) for current-tuning

NIST

Comment Superior of Strander the anal Security of



### **TDLAS Challenges**

- · Weak overtone molecular transitions
  - Need to measure τ ~0.99999
- Line shapes change with T & collision partners
- Congested spectra
  - H<sub>2</sub>O primary culprit
  - Hot bands at high temperatures
  - Unknown high-temperature spectroscopy
- Interferometric noise (etalons)
- Beam steering/optical alignment

- -Spatial Res.: Can be ~10 cm
- -Temporal Res.: Can be < 1 ms
- -Accuracy:
- $\tau$  of 0.99999 or 0.9999 achievable
- \*space/time/T trade-off
- •CO => 0.1% per m, 200 ms, 300 K

NIST

etianal testilute of Steenhards and Technology



### Year 2000 TDLAS Work Fires and Sooty Flames

- NIST
  - CO, C<sub>2</sub>H<sub>2</sub> => quantifying signals & determining uncertainty
- Army Research Laboratory (ARL)
  - HF, O<sub>2</sub>, hydrocarbons => suppressant effectiveness, fuel-to-air ratio
- Sandia National Laboratories (SNL)
  - H<sub>2</sub>O, soot, temperature, C<sub>2</sub>H<sub>2</sub>, CO<sub>2</sub> => real-scale fire hardware
- Naval Research Laboratory (NRL)
  - O<sub>2</sub> for large-scale suppression studies
- Stanford/Navy Pulse Detonation Engines
  - T, soot fraction, 2-color soot absorption/emission, multiplexed diodes

NIST

Extraord Santibute of Standards the and Bernathings accordings experiested to 1850. Department of Contract




#### **Near-IR TDLAS Success Stories**

- HF measured during chemical suppression of large Army <u>fires</u>— McNesby et al., Appl. Phys. B 67:443, 1998
- 10-kHz control system used to optimize a <u>50-kW Navy dump</u> <u>combustor</u>--Furlong et al., AIAA J. 37:732, 1999
- Air mass flux sensor flown on <u>P&W F-100 aircraft engine</u>—Allen, Meas. Science & Tech. 9:545 1999
- Hygrometer flown on wing of <u>NASA P3B research aircraft</u>--Applied Physics B. 67:275 Sonnenfroh et al., 1998
- O<sub>2</sub>, CO, and HCl in stack of a 27-MW paper mill boiler/incinerator, HF in <u>aluminum smelter</u>, NH<sub>3</sub> in 460-MW <u>coal boiler flue</u>, Linnerud, et al., Appl. Phys. B 67:297, 1998
- H<sub>2</sub>O & T in NASA microgravity <u>drop tower flames</u>—Silver et al., Appl. Opt. 34:2787
- CH<sub>4</sub> sensor in <u>landfill</u>--Hovde et al., J. Atm. Chem. 20:141, 1995

NST

tetianel testitute et Standords und Technology Erzeksor Autoriunaler, U.S. Desafonel al Communs





#### Summary

	Spatial Resolution	Temporal Resolution	Accuracy (?*)	Comments
Raman Scattering	~1 mm	< 1 µз	5 %	Weak Signals Multiple Species
Rayleigh Scattering	~1 mm	< 1 µs	5 %	Clean Environment
LIF	~1 mm	<1 με	5 %	Quenching Important
CARS	- 2 mm	<1 μs	5 %	Mild Soot OK Complex Data Reduction
LIBS	~ 2 mm	~100 µs	5 %	Metals/Toxicity
TDLAS	~10 cm	~1 ms	5 %	Space/Time/Temperature Trade-Off Fire Research Activity

\*Accuracy depends on species being measured and its environment, i.e., line strength, temperature dependence of spectroscopy, interfering species, averaging time, beam attenuatio and steering, dynamic range of detector, etc.

NS

telland testicle of Standards and technology



### Reading List I

- Laser Diagnostics for Studies of Turbulent Combustion. E.P. Hassel and S. Linow. Meas. Sci. Technol. 11:R37. 2000.
- Laser Spectroscopic Techniques for Combustion Diagnostics. Marcus Alden. Combust. Sci. Tech. 149:1. 1999.
- Laser and Probe Diagnostics in Fundamental Combustion Research. Katharina Kohse-Hoinghaus. Israel Journal of Chemistry. 39:25. 1999.
- Diode Laser Absorption Sensors for Gas-Dynamic and Combustion Flows. Mark Allen. Meas. Sci. Technol. 9:545. 1998.
- Diode Laser Based Measurements of Hydrogen Fluoride Gas During Chemical Suppression of Fires. K.L. McNesby, R. Reed Skaggs, A.W. Miziolek, M. Clay, S.H. Hoke, and C.S. Miser. Appl. Phys. B. 67:443, 1998.
- Laser Induced Fluorescence Spectroscopy in Flames. John Daily. Prog. Energy Comb. Sci. 23:133. 1997.
- Application of Tunable Excimer Lasers to Combustion Diagnostics: A Review.
   E.W. Rothe and P. Andresen. Applied Optics. 36:3971. 1997.

NS

Stational Southful of Standards to and Secondary Technology administration (U.S. Decompany of Contract



### **Reading List II**

- Applications of Laser-Induced Breakdown Spectroscopy. K. Song, Y.I. Lee, and J. Sneddon. Applied Spectroscopy Reviews. 32:183. 1997.
- <u>Laser Diagnostics for Combustion Temperature and Species Measurements</u>.
   Alan Eckbreth, Gordon & Breach, 1996.
- The Structure of Nonpremixed Flames Revealed by Raman-Rayleigh-LIF Measurements. A.R. Masri, R.W. Dibble, and R.S. Barlow. Prog. Energy Comb. Sci. 22:307. 1996.
- The Applications of Laser Rayleigh-Scattering to Combustion Diagnostics. F.Q. Zhao and H. Hiroyasu. *Prog. Energy Comb. Sci.* 19:447. 1993.
- Laser Measurements of Scalars in Turbulent Diffusion Flames. D. Stepowski. Prog. Energy Comb. Sci. 18:463. 1992.
- CARS in Combustion Prospects and Problems. B. Attaltretout, P. Bouchardy, P. Magre, M. Pealat, and J.P. Taran. Applied Physics B. 51:17. 1990.
- Planar Laser-Fluorescence Imaging of Combustion Gases.
   R.K. Hanson, J.M. Seitzman, and P.H. Paul. Applied Physics B. 50:441. 1990.

NIST

defiand trythire of Standards and Technology according Associated by U.S. Dissertion of Communic



### **Reading List III**

- Raman Spectroscopy in the Analysis of Fire Gases. M. Alden, J. Blomqvist, H. Edner, and H. Lundberg. Fire and Materials. 7:32. 1983.
- Laser Diagnostics Applied to Combustion Systems. S.S. Penner, C.P.
   Wang, and M.Y. Bahadori. 20th Combustion Symposium. p. 1149. 1984.
- Combustion Diagnostics by Laser Raman and Fluorescence Techniques.
   Alan Eckbreth, Paul Bonezyk, and James Verdieck. Prog. Energy Combust.
   Sci. 5:253. 1979.
- Raman Scattering Studies of Combustion. Marshall Lapp & Danny Hartley. Combust. Sci. and Technol. 13:199. 1976.
- Estimates of Possible Detection Limits for Combustion Intermediates and Products with Line-Center Absorption and Derivative Spectroscopy Using Tunable Lasers. K.G.P. Sulzmann, J.E.L. Lowder, and S.S. Penner. Combust. Flame. 20:177. 1973.

NIST

lactocalogy sythological phon, U.S. Department of Communica

